

# OSHA PENNANT FLAGS



## Product Specifications

Trinity Tape & Marking's OSHA Pennant Flags exceed the required 500 lb. break strength in all three color combinations. (Yellow, Red, Yellow/Red). They are required by OSHA for marking construction areas above ground especially on upper level construction and flat roofing.

### Product Type

- OSHA Pennant Flags
- OSHA – Regulation 1926-956(c)(1)

### Standards and Packaging

- Flag size: 12"x18"
- Flags per strand: 48
- Strand length: 105'
- Carton quantity: 10 strands
- Master quantity: 60 strands
- Pallet quantity: 15 master cases/900 strands
- Test Weight: 500 lb. min (Average after OSHA Testing – 586 lbs.)



### Physical Properties

Film Thickness-Flags / Strand	4 mil - Heavy Metal Free	ASTM D-2103 / ASTM D-4453
Density	0.922 (dm/cc)	ASTM D-792-66
Printability	≥ 45 Dynes	ASTM D-2578-08
Film Material	100% Virgin Polyethylene	Ultra High Molecular Weight
Flexibility	Pliable and shall remain pliable	ASTM D-671
Film Colors	OSHA Yellow/Red/White	Ultra High Molecular Weight
ASTM Break Strength	GB/T10454-2000	2500
Inner Rope Material	100% Virgin Polypropylene	Exceeds 500 lb. Break Strength